

STOPER DRILL

Because of the large diameter of the piston, these drills are equally efficient with low air pressure. It comes with a robust ratchet wheel rotation mechanism, short stroke, and good penetration in sand and medium-hard rock. The WR version with clockwise rotation can be used for nuts tightening when roof bolting. The drills are suitable for production drill, raise driving, and bolting.



Model #	RMT 46WS-8	RMT 46WS-6	RMT 3/30 SL
Weight (kg / lb)	40 kg / 88 lb	39 Kg / 86 lb	39 kg / 86 lb
Length retracted (mm / inch)	1650 mm / 65"	1435 mm / 56½"	1700 mm / 67"
Length extracted (mm / inch)	2620 mm / 103"	2205 mm / 86.8"	2580 mm / 102"
Air pressure (bar / psi)	6 bar / 87 psi	6 bar / 87 psi	6 bar / 87 psi
Air consumption (ls / cfm)	90 l/s / 191 cfm	90 l/s / 191 cfm	80 l/s / 150 cfm
Blows per minute	3000	3000	2900
Drilling depth (metre/inch)	-	-	3-4 metre / 10-12 ft.
Hole dia (mm/inch)	-	-	32mm / 1.25"
Piston dia (mm / inch)	75 mm / 3"	75 mm / 3"	76 mm / 3"
Piston stroke (mm / inch)	45 mm / 1¾"	45 mm / 1¾"	51 mm / 2"
Shank size (mm / inch)	22 x 108 mm / 7/8" x 4¼" (Hex)		22 x 108 mm / 7/8" x 4¼"
Air inlet (BSP) (mm / inch)	-	-	19 mm / 3/4"