

JACKLEG / PUSHERLEG DRILL

Rama Mining Tools Jackleg / pusherleg drills are a combination of high performance and reliability. It has low spare parts consumption so maintenance cost is at its minimum. Though simple to operate, they are robust and even with low air consumption, they offer high impact. Along with their pusher legs, they are proved to be cost saving drilling units without compromising on production.



RMT 656W



RMT 16W



RMT S215



RMT 3/30 JLD

| Model # | RMT 656W | RMT 16W | RMT 3/30 JLD | RMT S215 |
|-----------------------------|-------------------------|-------------------------|------------------------|------------------------|
| Weight (kg / lb) | 22 kg / 48.5 lb | 28.5 kg / 63 lb | 23 kg / 50.71 lb | 22.6 kg / 49.82 lb |
| Length (mm / inch) | 630 mm / 24.8" | 710 mm / 28" | 610 mm / 24" | 730 mm / 28.7" |
| Hole range (mm / inch) | 27 - 41 mm / 1" - 1.63" | 27 - 41 mm / 1" - 1.63" | - | - |
| Hole depth (metres / ft) | 6 metres / 19.6 ft | - | - | - |
| Air pressure (bar / psi) | 6 bar / 87 psi | 6 bar / 87 psi | - | - |
| Air consumption (l/s / cfm) | 48 l/s / 102 cfm | 69 l/s / 146 cfm | 57 l/s / 120 cfm | 55 l/s / 117 cfm |
| Blows per minutes | 2040 | 2340 | 2600 | - |
| Piston dia (mm / inch) | 65 mm / 2.56" | 70 mm / 2¾" | 76 mm / 3" | - |
| Piston stroke (mm / inch) | 60 mm / 2.36" | 55 mm / 2.17" | 51 mm / 2" | 55 mm / 2.16" |
| Air inlet (BSP) (mm / inch) | 19 mm / ¾" | 25 mm / 1" | 19 mm / ¾" BSP | - |
| Shank size (mm / inch) | 22 x 108 mm / ¾" x 4¼" | 22 x 108 mm / ¾" x 4¼" | 22 x 108 mm / ¾" x 4¼" | 22 x 108 mm / ¾" x 4¼" |