



RMT 4123



RMT 4125



RMT 4130



CP 4131



CP 0017 SVR



CP 0012



TEX 03 PS



TEX 05 P



TEX 05 PE



TEX 07 PE



TEX 12 PE

CHIPPING HAMMER

With highest specific BPM, RAMA MINING TOOLS range of Chipping Hammers / chippers are available in **2", 3" and 4" stroke**. It is also available with **Hex or Round shank**. These are most suitable for light surface renovation on soft material such as tile removal, swimming pool renovations, chipping, cutting and trimming etc. Comfort and safety of operator is placed on top without compromising on the sheer power of this Pneumatic Chipping Hammer. Most commonly used in **Foundry and Forge shops** and Mining and Construction related **light and medium-hard renovation and construction tasks**.

| Model # | RMT 4123 2H/2R | RMT 4123 3H/3R | RMT 4123 4H/4R | RMT 4125 2H/2R | RMT 4125 3H/3R | RMT 4125 4H/4R | RMT 4130 2H/2R | RMT 4130 3H/3R | RMT 4130 4H/4R |
|------------------------------------|------------------------|------------------------|------------------------|------------------------|------------------------|------------------------|--------------------------------|--------------------------------|--------------------------------|
| Weight (kg / lb) | 7 kg / 15 lb | 8 kg / 17.65 lb | 8.65 kg / 19 lb | 7 kg / 15.4 lb | 7.6 kg / 16.75 lb | 8.4 kg / 18.5 lb | 8.4 kg / 18.5 lb | 9 kg / 20 lb | 9.4 kg / 21 lb |
| Length (mm / inch) | 375 mm / 14.8" | 426 mm / 16.75" | 460 mm / 18.1" | 380 mm / 15" | 430 mm / 17" | 455 mm / 19" | 356 mm / 14" | 387 mm / 15.25" | 419 mm / 16.50" |
| Blows per minute | 2500 | 2050 | 1600 | 2100 | 1650 | 1375 | 3600 | 2280 | 1800 |
| Piston stroke (mm / inch) | 50.8 mm / 2" | 76.2 mm / 3" | 101.6 mm / 4" | 50.8 mm / 2" | 76.20 mm / 3" | 101.6 mm / 4" | 50.8 mm / 2" | 76.2 mm / 3" | 101.6 mm / 4" |
| Air pressure (bar / psi) | 6.2 bar / 90 PSI | 6.2 bar / 90 PSI | 6.2 bar / 90 PSI | 6.2 bar / 90 PSI | 6.2 bar / 90 PSI | 6.2 bar / 90 PSI | 6.2 bar / 90 PSI | 6.2 bar / 90 PSI | 6.2 bar / 90 PSI |
| Air consumptio (l/s / cfm) | 14 l/s / 30 cfm | 14 l/s / 30 cfm | 14 l/s / 30 cfm | 15.5 l/s / 33 cfm | 16 l/s / 34 cfm | 16.5 l/s / 35 cfm | 14 l/s / 30 cfm | 15.5 l/s / 33 cfm | 14 l/s / 30 cfm |
| Piston dia (mm / inch) | 28.6 mm / 1.13" | 28.6 mm / 1.13" | 28.6 mm / 1.13" | 28.6 mm / 1.13" | 28.6 mm / 1.13" | 28.6 mm / 1.13" | 28.6 mm / 1.13" | 28.6 mm / 1.13" | 28.6 mm / 1.13" |
| Air inlet (BSP thread) (mm / inch) | 9.5 mm / 3/8" | 9.5 mm / 3/8" | 9.5 mm / 3/8" | 9.5 mm / 3/8" | 9.5 mm / 3/8" | 9.5 mm / 3/8" | 22.2 mm / 7/8" (UNS thread) | 22.2 mm / 7/8" (UNS thread) | 22.2 mm / 7/8" (UNS thread) |
| Retainer type | Spring | Spring | Spring | Spring | Spring | Spring | Spring | Spring | Spring |
| Shank size (mm / inch) | Hex 14.7 mm / 0.580" | Hex 14.7 mm / 0.580" | Hex 14.7 mm / 0.580" | Hex 14.7 mm / 0.580" | Hex 14.7 mm / 0.580" | Hex 14.7 mm / 0.580" | Hex 14.7 mm / 0.580" | Hex 14.7 mm / 0.580" | Hex 14.7 mm / 0.580" |
| | Round 17.3 mm / 0.680" | Round 17.3 mm / 0.680" | Round 17.3 mm / 0.680" | Round 17.3 mm / 0.680" | Round 17.3 mm / 0.680" | Round 17.3 mm / 0.680" | Round 17.3 mm / 0.680" | Round 17.3 mm / 0.680" | Round 17.3 mm / 0.680" |
| Ref. Part # | 8900 0001 05 | 8900 0001 07 | 8900 0001 09 | 8900 0001 11 | 8900 0001 13 | 8900 0001 15 | - | - | - |

| Model # | CP 4131 3H/3R | CP 0017 SVR | CP 0012 | TEX 03 PS | TEX 05 P | TEX 05 PE | TEX 07 PE | TEX 12 PE |
|------------------------------------|--------------------------------|------------------------|------------------------|------------------|------------------|------------------------|------------------------|---------------------------|
| Weight (kg / lb) | 8.5 kg / 19 lb | 9.5 kg / 21 lb | 5.5 kg / 12 lb | 4 kg / 8.8 lb | 5.5 kg / 12.1 lb | 6.5 kg / 14.3 lb | 8.7 kg / 19.2 lb | 12 kg / 26.5 lb |
| Length (mm / inch) | 420 mm / 16½" | 540 mm / 21" | 406 mm / 16" | 300 mm / 11.8" | 380 mm / 15" | 450 mm / 17.7" | 525 mm / 20.7" | 590 mm / 23.2" |
| Blows per minute | 1920 | 1770 | 2580 | 4080 | 2760 | 2640 | 1770 | 1620 |
| Piston stroke (mm / inch) | 76.2 mm / 3" | - | - | - | - | - | - | - |
| Air pressure (bar / psi) | 6.2 bar / 90 PSI | 6.2 bar / 90 PSI | 6.2 bar / 90 PSI | 7 bar / 102 PSI | 7 bar / 102 PSI | - | - | - |
| Air consumptio (l/s / cfm) | 12 l/s / 25 cfm | 17 l/s / 36 cfm | 9.5 l/s / 20 cfm | 6.9 l/s / 15 cfm | 9.5 l/s / 20 cfm | 17 l/s / 36 cfm | 17 l/s / 36 cfm | 20 l/s / 0.71 cfm |
| Piston dia (mm / inch) | 28.6 mm / 1.13" | - | - | - | - | - | - | - |
| Air inlet (BSP thread) (mm / inch) | 22.2 mm / 7/8" (UNS thread) | 9.5 mm / 3/8" | 9.5 mm / 3/8" | - | - | - | - | - |
| Retainer type | Quick change | Screw cap | Screw type | Screw cap | Screw cap | cap | cap | cap |
| Shank size (mm / inch) | 14.7 mm / 0.580" | 19 x 50 mm / 3/4" x 2" | 19 x 50 mm / 3/4" x 2" | - | - | 19 x 50 mm / 3/4" x 2" | 19 x 50 mm / 3/4" x 2" | 22 x 82.5 mm / 7/8" x 3¼" |
| | 17.3 mm / 0.680" | | | | | | | 25 x 75 mm / 1" x 3" |