

CLAY DIGGER

Rama Mining Tools manufactured **Clay Diggers** are lighter but still, it has powerful blows per minute. These are widely accepted as an alternative to a Pneumatic Breaker because it can be used for overhead, vertical or horizontal jobs. These **RMT Clay Diggers** are mainly used for renovations of exterior brick walls, digging so ground and soils and some time for breaking rocks in tunnels or mines.

Model #	RMT CD22	RMT 222	CP 0111 CHLA
Weight (kg / lb)	11 kg / 24 lb	12 kg / 26 lb	13.5 kg / 30 lb
Length (mm / inch)	495 mm / 19.5"	533 mm / 21"	597 mm / 23.5"
Air pressure (bar / psi)	6.2 bar / 90 psi	6.2 bar / 90 psi	6.2 bar / 90 psi
Air consumption (l/s / cfm)	21 l/s / 45 cfm	19 l/s / 40 cfm	21 l/s / 45 cfm
Blows per minute	1320	1500	1,740 – 1,920
Piston dia (mm / inch)	40 mm / 1.60"	40 mm / 1.60"	-
Piston stroke (mm / inch)	44 mm / 1.73"	88 mm / 3.46"	-
Air inlet (BSP thread) (mm / inch)	19 mm / ¾"	19 mm / ¾"	9.5 mm / ⅜"
Shank size (Sq) (mm / inch)	19 x 82 mm / ¾" x 3¼"	-	-
Shank size (Hex) (mm / inch)	-	22 x 82.5 mm / ⅞" x 3¼"	25 x 108 mm / 1" x 4 ¼"
Retainer type	Screw cap	Latch	Latch



RMT CD22



RMT 222



CP 0111 CHLA