

The BBD 12D is a lightweight, 9.8 kg pneumatic rock drill featuring a D-type handle designed specifically for horizontal, plug-hole, and shallow concrete drilling up to one meter deep. It operates at an air consumption rate of 24 l/s with an impact rate of 2,580 blows per minute and includes a kick-latch retainer for fast steel changes. The drill is available in two shank sizes: 22 x 108 mm and 19 x 108 mm. Along with the original OEM model, RMT offers a cost-effective aftermarket alternative, the RMT 12D, which provides identical performance and interchangeable parts. For noise-sensitive applications, a silenced variant (BBD 12DS) is also available in the 19 x 108 mm shank size.



Specification

Model #	BBD 12D	
Weight	9.8 kg	22 lb
Length	565 mm	22.2"
Hole range	17 mm - 29 mm	0.67" - 1.14"
Hole depth	1 metre	3 ft
Air pressure	6 bar	87 psi
Air consumption	24 l/s	51 cfm
Blows per minute	2580	
Revolution	220 rpm	
Piston dia	45 mm	1.77"
Piston stroke	41 mm	1.61"
Shank size (Hex) - 8311 0102 96	22 x 108 mm	7/8" x 4 1/4"
Shank size (Hex) - 8311 0102 47	19 x 108 mm	3/4" x 4 1/4"
Manufacturer	OEM	

25 Sep 2026