



RMT 1210S



RMT 1230S



RMT PB 60



RMT 117



RMT 777



RMT 1240



RMT 117L



CP 0112



CP 0112 EXT



CP 1210 SVR



CP 1260



CP 1260 SVR



CP 1290



CP 1290 SVR



TEX 140 PS



RTEX 15



TEX 150 PE



TEX 20 PS



TEX 21 PE



TEX 190 PE



RTEX 25



TEX 230 PE



TEX 280 PE



RTEX 35



TEX P60S



TEX 33 PE



TEX 20 PS



TEX 39 PS



TEX P90S



TEX 40 PE

RMT pneumatic breakers are available in weights, ranging from **35 lb to 90 lb class (20 kg to 41 kg)**. The hammers are available with different shank size, varying from **25 mm to 32 mm shank (1" to 1¼")**. These air tools are capable of light, medium and heavy duty jobs such as demolition, construction, renovation, road construction, bridge work and street repairs. Depending on the job in hand, users will find the most suitable breaker in **RMT range**. Being considered as the "manufacturer of high quality Paving Breakers from India", all our breakers are manufactured with the goal of providing "Operator's safety, maximum power, maximum durability, easily serviceable and affordable price"

Model #	RMT 1210	RMT 1230	RMT PB 60	RMT 117	RMT 777	RMT 1290	RMT 1240	RMT 117 L	RMT 1290 SVR
Weight with silencer (kg / lb)	20 kg / 44 lb	30 kg / 66 lb	31.5 kg / 69 lb	37 kg / 81 lb	37.3 kg / 82 lb	39 kg / 86 lb	40 kg / 88 lb	41 kg / 91 lb	43.5 kg / 96 lb
Weight without silencer (kg / lb)	19.4 kg / 42.7 lb	29 kg / 64 lb	-	36 kg / 80 lb	-	37 Kg / 81 lb	39 kg / 86 lb	40 kg / 89 lb	-
Length (mm / inch)	609 mm / 24"	660 mm / 26"	645 mm / 25"	710 mm / 28"	715 mm / 28.15"	730 mm / 29"	718 mm / 28.25"	710 mm / 28"	785 mm / 31"
Air pressure (bar / psi)	6 bar / 87 psi	6 bar / 87 psi	-	6 bar / 87 psi	-	6 bar / 87 psi	6 bar / 87 psi	6 bar / 87 psi	6 bar / 87 psi
Air consumption (l/s / cfm)	23 l/s / 48 cfm	30 l/s / 65 cfm	27 l/s / 57 cfm	35 l/s / 74 cfm	34 l/s / 72 cfm	43 l/s / 91 cfm	38 l/s / 81 cfm	35 l/s / 74 cfm	43 l/s / 91 cfm
Blows per minute	1450	1350	1400	1200	1100	1100	1250	1200	1300
Piston dia (mm / inch)	48 mm / 1.90"	60.3 mm / 2.40"	57.15 mm / 2.25"	57 mm / 2.25"	57 mm / 2.24"	-	67 mm / 2.63"	57 mm / 2.25"	-
Piston stroke (mm / inch)	108 mm / 4.25"	140 mm / 5.50"	100 mm / 4"	165 mm / 6.50"	189 mm / 7.44"	-	158 mm / 6.25"	165 mm / 6.50"	-
Shank size (mm / inch) - Std	25 x 108 mm / 1" x 4 1/4"	32 x 160 mm / 1 1/4" x 6 3/4"	32 x 160 mm / 1 1/4" x 6 3/4"	32 x 160 mm / 1 1/4" x 6 3/4"	32 x 160 mm / 1 1/4" x 6 3/4"	32 x 160 mm / 1 1/4" x 6 3/4"	32 x 160 mm / 1 1/4" x 6 3/4"	32 x 160 mm / 1 1/4" x 6 3/4"	32 x 160 mm / 1 1/4" x 6 3/4"
Shank size (mm / inch) Option- 1	-	28 x 160 mm / 1 1/8" x 6 3/4"	28 x 160 mm / 1 1/8" x 6 3/4"	28 x 160 mm / 1 1/8" x 6 3/4"	-	28 x 160 mm / 1 1/8" x 6 3/4"	28 x 160 mm / 1 1/8" x 6 3/4"	28 x 160 mm / 1 1/8" x 6 3/4"	28 x 160 mm / 1 1/8" x 6 3/4"
Shank size (mm / inch) Option- 2	-	-	-	-	-	-	-	-	-
Retainer type	Latch	Latch	Latch	Spring	Hinged U-Latch Type	Latch	Latch	Latch	Latch

Model #		CP 0112	CP 0112 EXT	CP 1210 SVR	CP 1260	CP 1260 SVR	TEX 140 PS	RTEX 15	TEX 150 PE
Weight with silencer (kg / lb)		14.5 kg / 32 lb	16 kg / 35 lb	24.5 kg / 55 lb	31 kg / 68 lb	34 kg / 75 lb	15.5 kg / 34 lb	17 kg / 37.4 lb	19 kg / 41 lb
Weight without silencer (kg / lb)		13.5 kg / 30 lb	-	-	29 Kg / 64 lb	-	-	-	-
Length (mm / inch)		535 mm / 21"	800 mm / 31.5"	600 mm / 24"	680 mm / 26.7"	735 mm / 29"	590 mm / 23.2"	674 mm / 26.5"	590 mm / 23.2"
Air pressure (bar / psi)		6 bar / 87 psi	6 bar / 87 psi	6 bar / 87 psi	6 bar / 87 psi	6 bar / 87 psi	-	-	-
Air consumption (l/s / cfm)		23 l/s / 49 cfm	23 l/s / 49 cfm	26.5 l/s / 56 cfm	34.5 l/s / 73 cfm	34.5 l/s / 73 cfm	25 l/s / 53 cfm	15.4 l/s / 32.6 cfm	25 l/s / 52 cfm
Blows per minute		1620	1620	1400	1300	1300	1530	936	1530
Piston dia (mm / inch)		-	-	-	-	-	-	-	-
Piston stroke (mm / inch)		-	-	-	-	-	-	-	-
Shank size (mm / inch) - Std		25 x 108 mm / 1" x 4 1/4"	25 x 108 mm / 1" x 4 1/4"	25 x 108 mm / 1" x 4 1/4"	32 x 160 mm / 1 1/4" x 6 3/4"	32 x 160 mm / 1 1/4" x 6 3/4"	22 x 82.5 mm / 7/8" x 3 1/4"	25 x 108 mm / 1" x 4 1/4"	25 x 108 mm / 1" x 4 1/4"
Shank size (mm / inch) Option- 1		-	-	28 x 160 mm / 1 1/8" x 6 3/4"	28 x 160 mm / 1 1/8" x 6 3/4"	28 x 160 mm / 1 1/8" x 6 3/4"	25 x 108 mm / 1" x 4 1/4"	-	22 x 82.5 mm / 7/8" x 3 1/4"
Shank size (mm / inch) Option- 2		-	-	32 x 160 mm / 1 1/4" x 6 3/4"	-	-	-	-	-
Retainer type		Latch	Latch	Latch	Latch	Latch	Latch	Latch	Latch

Model #	TEX 20 PS	TEX 21 PE	TEX 190 PE	RTEX 25	TEX 230 PE	TEX 280 PE	RTEX 35	TEX P60S	TEX 33 PE
Weight with silencer (kg / lb)	20 kg / 44 lb	21 kg / 46 lb	23 kg / 51 lb	25 kg / 55 lb	25.5 kg / 56 lb	31.5 kg / 69 lb	33.2 kg / 73.2 lb	33 kg / 73 lb	37 kg / 82 lb
Weight without silencer (kg / lb)	-	-	-	-	-	-	-	31 kg / 68 lb	-
Length (mm / inch)	635 mm / 25"	650 mm / 25.6"	595 mm / 23.4"	780 mm / 31"	625 mm / 24.6"	690 mm / 27.2"	845 mm / 33.3"	690 mm / 27.2"	745 mm / 29.3"
Air pressure (bar / psi)	7 bar / 102 psi	-	-	7 bar / 102 psi	-	-	-	7 bar / 102 psi	-
Air consumption (ls / cfm)	25 l/s / 53 cfm	25 l/s / 52 cfm	26 l/s / 55 cfm	18.5 l/s / 39.2 cfm	30 l/s / 64 cfm	32 l/s / 64 cfm	21.5 l/s / 45.5 cfm	36 l/s / 76 cfm	34 l/s / 72 cfm
Blows per minute	1140	1140	1500	870	1320	1230	660	1500	1200
Piston dia (mm / inch)	-	-	-	-	-	-	-	-	-
Piston stroke (mm / inch)	-	-	-	-	-	-	-	-	-
Shank size (mm / inch) - Std	25 x 108 mm / 1" x 4 1/4"	25 x 108 mm / 1" x 4 1/4"	25 x 108 mm / 1" x 4 1/4"	32 x 160 mm / 1 1/4" x 6 3/4"	32 x 160 mm / 1 1/4" x 6 3/4"	32 x 160 mm / 1 1/4" x 6 3/4"	32 x 160 mm / 1 1/4" x 6 3/4"	32 x 160 mm / 1 1/4" x 6 3/4"	32 x 160 mm / 1 1/4" x 6 3/4"
Shank size (mm / inch) Option- 1	-	-	28 x 160 mm / 1 1/8" x 6 3/4"	28 x 160 mm / 1 1/8" x 6 3/4"	28 x 160 mm / 1 1/8" x 6 3/4"	28 x 160 mm / 1 1/8" x 6 3/4"	28 x 160 mm / 1 1/8" x 6 3/4"	28 x 160 mm / 1 1/8" x 6 3/4"	28 x 160 mm / 1 1/8" x 6 3/4"
Shank size (mm / inch) Option- 2	-	-	-	-	25 x 108 mm / 1" x 4 1/4"	-	-	-	-
Retainer type	Latch	Latch	Latch	Lock retainer	Latch	Latch	Notch latch	Latch	Latch

Model #	TEX 37	TEX 39 PS	TEX P90S	TEX 40 PE
Weight with silencer (kg / lb)	37 kg / 81 lb	39 kg / 86 lb	43 kg / 95 lb	42 kg / 93 lb
Weight without silencer (kg / lb)	-	-	41 kg / 90 lb	-
Length (mm / inch)	729 mm / 29"	750 mm / 29.5"	710 mm / 28"	750 mm / 29.5"
Air pressure (bar / psi)	7 bar / 102 psi	-	7 bar / 102 psi	-
Air consumption (ls / cfm)	35 l/s / 74 cfm	40 l/s / 85 cfm	40 l/s / 85 cfm	40 l/s / 85 cfm
Blows per minute	1200	1110	1260	1110
Piston dia (mm / inch)	-	-	-	-
Piston stroke (mm / inch)	-	-	-	-
Shank size (mm / inch) - Std	32 x 160 mm / 1 1/4" x 6 3/4"	32 x 160 mm / 1 1/4" x 6 3/4"	32 x 160 mm / 1 1/4" x 6 3/4"	32 x 160 mm / 1 1/4" x 6 3/4"
Shank size (mm / inch) Option- 1	-	28 x 160 mm / 1 1/8" x 6 3/4"	28 x 160 mm / 1 1/8" x 6 3/4"	28 x 160 mm / 1 1/8" x 6 3/4"
Shank size (mm / inch) Option- 2	-	-	-	-
Retainer type	Latch	Latch	Latch	Latch