

Just like RMT 4123 series of chipping hammers, **RMT 4125 series of Chippers** too available with 2", 3" and 4" cylinder options and also with bushing choice of "Round" or "Hex". Its **unique ring valve design** provides a harder blow in blow in tough conditions. The **spline locking system** is there for extra safety as it prevents loosening of handle or cylinder. It has the same features like **lightweight, compact yet powerful**. This too has a pistol-grip handle with the self-closing outside trigger.



What is good about it?

- Straight forward design for easy maintenance
- Teasing throttle for precise control
- Rugged hardened steel cylinder and handle
- Choice of bushings

Where it is used?

- **In Mining and Construction**
 - Light concrete demolition
 - Roughening concrete surface
 - Scaling and scrubbing concrete and metal surfaces
 - Chip cement adhering to plant and vehicles
- **In Foundry and Forge**
 - Chipping and dressing concrete, caulking, fettling and deflashing casting & forgings


Lubricator

Working Tools

Spare Parts

Specification

Model #	RMT 4125 2H/2R		RMT 4125 3H/3R		RMT 4125 4H/4R	
Weight	7 kg	15.4 lb	7.6 kg	16.75 lb	8.4 kg	18.5 lb
Length	380 mm	15"	430 mm	17"	455 mm	19"
Air pressure	6.2 bar	90 psi	6.2 bar	90 psi	6.2 bar	90 psi
Air consumption	15.5 l/s	33 cfm	16 l/s	34 cfm	16.5 l/s	35 cfm
Blows per minute	2100		1650		1375	
Piston dia	28.6 mm	1.13"	28.6 mm	1.13"	28.6 mm	1.13"
Piston stroke	50.8 mm	2"	76.2 mm	3"	101.6 mm	4"
Air inlet (BSP thread)	9.5 mm	3/8"	9.5 mm	3/8"	9.5 mm	3/8"
Shank size (Hex) - 8900 0001 11	14.7 mm	0.580"	14.7 mm	0.580"	14.7 mm	0.580"
Shank size (Round) - 8900 0001 10	17.3 mm	0.680"	17.3 mm	0.680"	17.3 mm	0.680"
Retainer type	Spring		Spring		Spring	