

Likewise RMT 1260 breakers, these CP 1290 breakers too are more powerful and lighter in weight than the previous version RMT 1240. These CP 1290 breakers are heavy-duty, robust, and well suited for tough construction and plant maintenance work such as breaking reinforced concrete, heavy road work, cutting tarmac, frozen ground, or non-consolidated rock and for general demolition work. CP 1290 SVR is similar to this model. It comes with upgraded features like "Silencer and Vibration reduced handle".



What is good about it?

- Four-bolt-backhead-withstands rugged use
- Forged latch type retainer
- Easy access to daily service points
- Heavy-duty fronthead springs reduce reaction back o operator
- Reversible piston reduces maintenance cost
- "Goose neck" Air Inlet Swivel for easy handling and positioning

Where it is used?

- Extra Heavy Duty Concrete Demolition
- Consolidating and amming backfill and earth

Specification

Model #	CP 1290 / 1290 S	
Weight with silencer	39 kg	86 lb
Weight without silencer	37 Kg	81 lb
Length	730 mm	29"
Air pressure	6 bar	87 psi
Air consumption	43 l/s	91 cfm
Blows per minute	1100	
Air inlet	19 mm	¾"
Shank size (standard) 8900 0030 37, 8900 0030 39	32 x 160 mm	1¼" x 6¼"
Shank size (option 1) 8900 0030 38, 8900 0030 40	28 x 160 mm	1⅝" x 6¼"
Retainer type	Latch	

03 Sep 2026


Working Tools
Lubricator
Spare Parts
