

**RMT 4608 D and RMT 4611 D Rivet Busters** are low weighted but heavy-duty powerful hammers with teasing throttle. They are available with D-Handle with an inside trigger. Both models also have a **stepped cylinder design** to prevent accidental ejection of the piston from the cylinder. These busters are used for removing rivets and in metal and concrete applications, including demolition and bridgework. **Piston stroke of RMT 4608 D is 8" whereas, for RMT 4611 D, it is 11"**.



### What is good about it?

- Perfect tool for variety of concrete and metal applications
- Forged steel handle and hardened piston for long life in rugged conditions
- Stepped cylinder for extra safety
- Available with chromed cylinder or black barrel
- Can be used horizontally too

### Where it is used?

- Cutting and removing large rivets and bolts
- Cutting Metal tanks or plates
- Bridge deck work where breaker weight is a problem
- De-capping foundation pillars on hard concrete
- Medium to heavy concrete renovation

### Specification

Model #	RMT 4608 D		RMT 4611 D	
Weight	14.4 kg	31.7 lb	15.4 kg	34 lb
Length	600 mm	23.6"	676 mm	26.6"
Air pressure	6.2 bar	90 psi	6.2 bar	90 psi
Air consumption	21 l/s	44.5 cfm	21 l/s	44.5 cfm
Blows per minute	900		720	
Piston dia	30.2 mm	1.19"	30.2 mm	1.19"
Piston stroke	203 mm	8"	279 mm	11"
Air inlet (NPTF thread)	12.7 mm	½"	12.7 mm	½"
Reference #	8900 0001 49		8900 0001 52	
Shank size	Jumbo		Jumbo	



Lubricator



Working Tools



Spare Parts

31 Mar 2023 | RMT 100.03.02