

The CP 1290 SVR is an OEM 90 lb-class Chicago Pneumatic paving breaker engineered for heavy-duty demolition tasks like reinforced concrete, bridge deck removal, and major road breaking. It features an SVR vibration-reduction handle system to protect operators during long shifts, as well as an integral oiler and a four-bolt backhead for easy field maintenance. Supplied by RMT, it comes with complete spare parts support alongside options for 100% equivalent models and jackhammers ranging from 20 lb to 40 lb.



What is good about it?

- Four-bolt-backhead-withstands rugged use
- Forged latch type retainer
- Easy access to daily service points
- Heavy-duty fronthead springs reduce reaction back operator
- Reversible piston reduces maintenance cost
- "Goose neck" Air Inlet Swivel for easy handling and positioning

Where it is used?

- Extra Heavy Duty Concrete Demolition
- Consolidating and amming backfill and earth

Specification

Model #	CP 1290 SVR	
Weight with silencer	43.5 kg	96 lb
Length	785 mm	31"
Air pressure	6 bar	87 psi
Air consumption	43 l/s	91 cfm
Blows per minute	1300	
Air inlet	19 mm	¾"
Shank size (standard) 8900 0030 41	32 x 160 mm	1¼" x 6¼"
Shank size (option) 8900 0030 42	28 x 160 mm	1¼" x 6¼"
Retainer type	Latch	



Working Tools



Lubricator



Spare Parts

