



## **LUBRICATORS (1.3 ltr - 20ltr)**

*It's highly recommended to use a lubricator while using pneumatic jackhammer like Rock Drill or Paving Breakers. This external oil bottles allow rock drill oil to flow with air ,generated by air compressor. Once inside the hammer, it makes a film of oil which lubricates all internal parts of the jackhammer. This results in lesser wear and tear of the parts and tools performance also increases. It is also advisable to use it with the tools which has in built lubrication system. In-built lubrication system is not enough to keep lubrication in the parts for long.*

Ltr.	Model #	Oil volume		Hose connection		Air flow		Max pressure		Height		Outside dia	
		litre	gallon	mm	inch	l/s	cfm	bar	psi	mm	inch	mm	inch
1.3 Ltr.													
	RMT 30	1.3	0.29	25	1	25 - 130	53 - 282	20	290	-	-	-	-
2 Ltr.	2 L	2	0.44	38	1½	283	600	10	150	350	13.8	158	6.2
3 Ltr.	3 L	3	0.66	38.10	1½	282	600	10.34	150	430	17	165	6.5
	3 LA	3	0.66	50.80	2	423	900	13.79	200	430	17	165	6.5
5 Ltr.	5 L	5	1.1	63.50	1½ or 2	282	600	10.34	150	400	15.8	210	8.3
	5 LA	5	1.1	50.80	2	423	900	13.79	200	400	15.8	209	8.2
7 Ltr.	7 L	7	1.54	38 or 50.8	1½ or 2	283	600	10	150	450	17.72	209	8.23
10 Ltr.	10 L	10	2.2	50.8	2	282	600	10.34	150	580	22.8	210	8.3
	10 LA	10	2.2	50.8	2	352.5	750	17.24	250	585	23	210	8.3
	10 LB	10	2.2	50.8	2	423	900	17.24	250	585	23	210	8.3
	10 LC	10	2.2	50.8	2	423	900	24.13	350	585	23	210	8.3
	10 LD	10	2.2	63.5	2½	423	900	24.13	350	585	23	210	8.3
13.5 Ltr.	13.5 L	13.5	3.6	50.8	2	282	600	10.34	150	700	27.56	210	8.3
	13.5 LA	13.5	3.6	50.8	2	353	750	17.24	250	700	27.56	210	8.3
	13.5 LB	13.5	3.6	63.5	2½	423	900	24.13	350	700	27.56	210	8.3
	13.5 LC	13.5	3.6	63.5	2½	470	1000	24.13	350	700	27.56	210	8.3
	13.5 LD	13.5	3.6	63.5	2½	564	1200	24.13	350	700	27.56	210	8.3
	13.5 LE	13.5	3.6	63.5	2½	658	1400	24.13	350	700	27.56	210	8.3
15 Ltr.	15 L	15	3.9	50.8	2	282	600	10.34	150	725	28.54	210	8.3
	15 LA	15	3.9	50.8	2	329	700	17.24	250	725	28.54	210	8.3
	15 LB	15	3.9	50.8	2	423	900	17.24	250	725	28.54	210	8.3
	15 LC	15	3.9	63.5	2½	423	900	24.13	350	725	28.54	210	8.3
	15 LD	15	3.9	63.5	2½	470	1000	24.13	350	725	28.54	210	8.3
	15 LE	15	3.9	63.5	2½	564	1200	24.13	350	725	28.54	210	8.3
	15 LF	15	3.9	63.5	2½	658	1400	24.13	350	725	28.54	210	8.3
20 Ltr.	20 L	20	5.28	63.5	2½	423	900	24.13	350	680	26.77	273	10.75
	20 LA	20	5.28	63.5	2½	470	1000	24.13	350	680	26.77	273	10.75
	20 LB	20	5.28	63.5	2½	564	1200	24.13	350	680	26.77	273	10.75
	20 LC	20	5.28	63.5	2½	658	1400	24.13	350	680	26.77	273	10.75