

Rotary Drill

Rama Mining Tools provides a range of compact and lightweight plughole drills/ **Rotary Drills** which includes tools capable of drilling holes from 8 mm to 44 mm and for use in light chipping applications. The **RMT 009** is the “mother” of small rotary drills. It is the best air tool available on the market because of its super performance for such a small and easy-to-use drill. The other tool in the small rotary drill category is RMT 0014RR. These rotary hammers are used in a wide variety of construction and maintenance applications. A few examples are driving or setting masonry anchors and drilling holes in concrete, bricks, or rock. Like a hammer, these tools can also be used for chipping, scarifying, scaling, and cleaning welds so also called rotary hammers.



Model #	RMT 009	RMT 0014 RR	CP 0009A	DKR 36	CP 0009 CS
Weight (kg / lb)	4.5 kg / 10 lb	6.5 kg / 14.3 lb	4 kg / 9 lb	4.5 kg / 10 lb	5 kg / 9.9 lb
Length (mm / inch)	380 mm / 15"	480 mm / 19"	375 mm / 14.8"	375 mm / 14.8"	375 mm / 14.8"
Hole range (mm / inch)	32 mm / 1.26 "	44 mm / 1.73 "	32 mm / 1.26"	-	32 mm / 1.26
Hole depth (mm / inch)	450 mm / 17.7 "	650 mm / 25.6 "	450 mm / 17.7 "	-	450 mm / 17.7 "
Air pressure (bar / psi)	6.2 bar / 90 psi	6.2 bar / 90 psi	6.2 bar / 90 psi	6.2 bar / 90 psi	6.2 bar / 90 psi
Air consumption (l/s / cfm)	9 l/s / 19 cfm	22 l/s / 47 cfm	9 l/s / 19 cfm	10 l/s / 21 cfm	9.5 l/s / 20 cfm
Blows per minute	3420	2520	3420	2820	3420
Revolutions	189 rpm	165 rpm	189 rpm	250 rpm	189 rpm
Air inlet	9.5 mm / 3/8"	9.5 mm / 3/8"	9.5 mm / 3/8"	-	9.5 mm / 3/8"
Shank size (mm / inch) - Rd	19 x 95 mm / 3/4" x 3 3/4"	-	19 x 95 mm / 3/4" x 3 3/4"	19 x 95 mm / 3/4" x 3 3/4"	19 x 95 mm / 3/4" x 3 3/4"
Shank size (mm / inch) - Hex	-	22 x 82.5 mm / 7/8" x 3 1/4"	-	14.7 x 89 mm / 0.580" x 3 1/2"	-
Retainer type	Quick change	Spring	Quick change	-	Quick change