

CP 4608 D and CP 4611 D Rivet Busters are low weighted but heavy-duty powerful hammers with teasing throttle. They are available with D-Handle with an inside trigger. Both models also have a **stepped cylinder design** to prevent accidental ejection of the piston from the cylinder. These busters are used for removing rivets and in metal and concrete applications, including demolition and bridgework. **Piston stroke of CP 4608 D is 8" whereas, for CP 4611 D, it is 11"**.



What is good about it?

- ✦ Perfect tool for variety of concrete and metal applications
- ✦ Forged steel handle and hardened piston for long life in rugged conditions
- ✦ Stepped cylinder for extra safety
- ✦ Available with chromed cylinder or black barrel
- ✦ Can be used horizontally too

Where it is used?

- ✦ Cutting and removing large rivets and bolts
- ✦ Cutting Metal tanks or plates
- ✦ Bridge deck work where breaker weight is a problem
- ✦ De-capping foundation pillars on hard concrete
- ✦ Medium to heavy concrete renovation

Specification

Model #	CP 4608 D		CP 4611 D	
Weight	14.4 kg	31.7 lb	15.4 kg	34 lb
Length	600 mm	23.6"	676 mm	26.6"
Air pressure	6.2 bar	90 psi	6.2 bar	90 psi
Air consumption	21 l/s	44.5 cfm	21 l/s	44.5 cfm
Blows per minute	900		720	
Piston dia	30.2 mm	1.19"	30.2 mm	1.19"
Piston stroke	203 mm	8"	279 mm	11"
Air inlet (NPTF thread)	12.7 mm	½"	12.7 mm	½"
Reference #	8900 0001 51		8900 0001 52	
Shank size	Jumbo		Jumbo	



Lubricator



Working Tools



Spare Parts

12 AUG 2026