

RMT 4130 series of chipping hammers have a locking mechanism with **four bolts** which gives higher airflow and ease of service to the tool. It comes with a 'D' handle with the outside trigger. RMT 4130 series 4 bolt chippers are available in **2", 3", and 4" cylinder options** and with **"Round" or "Hex" shanks** to choose from. Hex shank prevents chisel rotation. This chipper comes with a muffler assembly. Its unique ring valve design provides a harder blow in tough conditions. The spline locking system is there for extra safety as it prevents loosening of the handle or cylinder.



### What is good about it?

- High strength back head for heavy-duty chipping, cutting and trimming
- 4-bolt flange increases durability, strength and ease of service
- Easy disassembling for maintenance
- Includes muffler

### Where it is used?

- Light concrete demolition
- Roughening concrete surface
- Chipping and dressing concrete, Fettling and deflashing castings and forgings
- Scaling and scrubbing concrete and metal surfaces



Lubricator



Working Tools



Spare Parts

### Specification

Model #	RMT 4130 2H/2R		RMT 4130 3H/3R		RMT 4130 4H/4R	
Weight	8.4 kg	18.5 lb	9 kg	20 lb	9.4 kg	21 lb
Length	356 mm	14"	387 mm	15.25"	419 mm	16.50"
Air pressure	6.2 bar	90 psi	6.2 bar	90 psi	6.2 bar	90 psi
Air consumption	14 l/s	30 cfm	15.5 l/s	33 cfm	16 l/s	34 cfm
Blows per minute	3600		2280		1800	
Piston dia	28.6 mm	1.13"	28.6 mm	1.13"	28.6 mm	1.13"
Piston stroke	50.8 mm	2"	76.2 mm	3"	101.6 mm	4"
Air inlet (BSP) - Standard	9.5 mm	3/4"	9.5 mm	3/4"	9.5 mm	3/4"
Air inlet (UNS) - Optional	22.2 mm	7/8"	22.2 mm	7/8"	22.2 mm	7/8"
Shank Size (Hex)	14.7 mm	0.580"	14.7 mm	0.580"	14.7 mm	0.580"
Shank Size (Round)	17.3 mm	0.680"	17.3 mm	0.680"	17.3 mm	0.680"
Retainer type	Spring		Spring		Spring	