



RMT 66



RMT 73



RMT 05 P



RMT 4123



RMT 4125



RMT 4130



RMT RI 9A



CP 4131



CP 0017 SVR



CP 0012



TEX 03 PS



TEX 05 P



TEX 05 PE



TEX 07 PE

CHIPPING HAMMER

With highest specific BPM, RAMA MINING TOOLS range of Chipping Hammers / chippers are available in **2", 3" and 4" stroke**. It is also available with **Hex or Round shank**. These are most suitable for light surface renovation on soft material such as tile removal, swimming pool renovations, chipping, cutting and trimming etc. Comfort and safety of operator is placed on top without compromising on the sheer power of this Pneumatic Chipping Hammer. Most commonly used in **Foundry and Forge shops** and Mining and Construction related **light and medium-hard renovation and construction tasks**.

Model #	RMT 66	RMT 73	RMT 05 P	RMT 4123 2H/2R	RMT 4123 3H/3R	RMT 4123 4H/4R	RMT 4125 2H/2R	RMT 4125 3H/3R	RMT 4125 4H/4R
Weight (kg / lb)	5.5 kg / 12 lb	8.5 kg / 19 lb	5.5 kg / 12 lb	7 kg / 15 lb	8 kg / 17.65 lb	8.65 kg / 19 lb	7 kg / 15.4 lb	7.6 kg / 16.75 lb	8.4 kg / 18.5 lb
Length (mm / inch)	430mm / 16.9"	460 mm / 18.1"	380 mm / 15"	375 mm / 14.8"	426 mm / 16.75"	460 mm / 18.1"	380 mm / 15"	430 mm / 17"	455 mm / 19"
Blows per minute	2000	1650	2760	2500	2050	1600	2100	1650	1375
Piston stroke (mm / inch)	-	-	-	50.8 mm / 2"	76.2 mm / 3"	101.6 mm / 4"	50.8 mm / 2"	76.20 mm / 3"	101.6 mm / 4"
Air pressure (bar / psi)	-	-	7 bar / 102 PSI	6.2 bar / 90 PSI	6.2 bar / 90 PSI	6.2 bar / 90 PSI	6.2 bar / 90 PSI	6.2 bar / 90 PSI	6.2 bar / 90 PSI
Air consumption (l/s / cfm)	18 l/s / 38 cfm	18 l/s / 38 cfm	9.5 l/s / 20 cfm	14 l/s / 30 cfm	14 l/s / 30 cfm	14 l/s / 30 cfm	15.5 l/s / 33 cfm	16 l/s / 34 cfm	16.5 l/s / 35 cfm
Piston dia (mm / inch)	-	-	-	28.6 mm / 1.13"	28.6 mm / 1.13"	28.6 mm / 1.13"	28.6 mm / 1.13"	28.6 mm / 1.13"	28.6 mm / 1.13"
Air inlet (BSP thread) (mm / inch)	-	-	-	9.5 mm / ⅜"	9.5 mm / ⅜"	9.5 mm / ⅜"	9.5 mm / ⅜"	9.5 mm / ⅜"	9.5 mm / ⅜"
Retainer type	Screw cap	Screw cap	Screw cap	Spring	Spring	Spring	Spring	Spring	Spring
Shank size (mm / inch)	21 x 12 mm	23 x 14 mm	19 x 50 mm / 3/4" x 2"	Hex 14.7 mm / 0.580"	Hex 14.7 mm / 0.580"	Hex 14.7 mm / 0.580"	Hex 14.7 mm / 0.580"	Hex 14.7 mm / 0.580"	Hex 14.7 mm / 0.580"
				Round 17.3 mm / 0.680"	Round 17.3 mm / 0.680"	Round 17.3 mm / 0.680"	Round 17.3 mm / 0.680"	Round 17.3 mm / 0.680"	Round 17.3 mm / 0.680"
Ref. Part #	-	-	8461 0219 00	8900 0001 05 8900 0001 04	8900 0001 07 8900 0001 06	8900 0001 09 8900 0001 08	8900 0001 11	8900 0001 13	8900 0001 15

Model #	RMT 4130 2H/2R	RMT 4130 3H/3R	RMT 4130 4H/4R	RMT RI 9A	CP 4131 3H/3R	CP 0017 SVR	CP 0012	TEX 03 PS	TEX 05 P
Weight (kg / lb)	8.4 kg / 18.5 lb	9 kg / 20 lb	9.4 kg / 21 lb	9 kg / 20 lb	8.5 kg / 19 lb	9.5 kg / 21 lb	5.5 kg / 12 lb	4 kg / 8.8 lb	5.5 kg / 12.1 lb
Length (mm / inch)	356 mm / 14"	387 mm / 15.25"	419 mm / 16.50"	520 mm / 20.47"	420 mm / 16½"	540 mm / 21"	406 mm / 16"	300 mm / 11.8"	380 mm / 15"
Blows per minute	3600	2280	1800	1200	1920	1770	2580	4080	2760
Piston stroke (mm / inch)	50.8 mm / 2"	76.2 mm / 3"	101.6 mm / 4"	-	76.2 mm / 3"	-	-	-	-
Air pressure (bar / psi)	6.2 bar / 90 PSI	6.2 bar / 90 PSI	6.2 bar / 90 PSI	-	6.2 bar / 90 PSI	6.2 bar / 90 PSI	6.2 bar / 90 PSI	7 bar / 102 PSI	7 bar / 102 PSI
Air consumptio (l/s / cfm)	14 l/s / 30 cfm	15.5 l/s / 33 cfm	14 l/s / 30 cfm	18.3 l/s / 38.8 cfm	12 l/s / 25 cfm	17 l/s / 36 cfm	9.5 l/s / 20 cfm	6.9 l/s / 15 cfm	9.5 l/s / 20 cfm
Piston dia (mm / inch)	28.6 mm / 1.13"	28.6 mm / 1.13"	28.6 mm / 1.13"	-	28.6 mm / 1.13"	-	-	-	-
Air inlet (BSP thread) (mm / inch)	22.2 mm / ⅞" (UNS thread)	22.2 mm / ⅞" (UNS thread)	22.2 mm / ⅞" (UNS thread)	-	22.2 mm / ⅞" (UNS thread)	9.5 mm / ⅜"	9.5 mm / ⅜"	-	-
Retainer type	Spring	Spring	Spring	-	Quick change	Screw cap	Screw type	Screw cap	Screw cap
Shank size (mm / inch)	Hex 14.7 mm / 0.580"	Hex 14.7 mm / 0.580"	Hex 14.7 mm / 0.580"	23 x 70 mm / ⅞"" x 2.7"	14.7 mm / 0.580"	19 x 50 mm / ¾" x 2"	19 x 50 mm / ¾" x 2"	19 x 50 mm / ¾" x 2"	19 x 50 mm / ¾" x 2"
	Round 17.3 mm / 0.680"	Round 17.3 mm / 0.680"	Round 17.3 mm / 0.680"		17.3 mm / 0.680"				
Ref. Part #	-	-	-		8900 0001 33	8900 0001 35	8900 0001 01	8461 0208 01	8461 0219 00

Model #	TEX 05 PE	TEX 07 PE
Weight (kg / lb)	6.5 kg / 14.3 lb	8.7 kg / 19.2 lb
Length (mm / inch)	450 mm / 17.7"	525 mm / 20.7"
Blows per minute	2640	1770
Piston stroke (mm / inch)	-	-
Air pressure (bar / psi)	-	-
Air consumption (l/s / cfm)	17 l/s / 36 cfm	17 l/s / 36 cfm
Piston dia (mm / inch)	-	-
Air inlet (BSP thread) (mm / inch)	-	-
Retainer type	Cap	Cap
Shank size (mm / inch)	19 x 50 mm / ¾" x 2"	19 x 50 mm / ¾" x 2"
Ref. Part #	8461 0219 10	8461 0209 20