

SCABBLERS

The RMT Scabbler's are equipped with a Tungsten-carbide piston which gives you a long and non-disruptive performance. The different designs of RMT Scabbler's gives you the opportunity to select as per your work requirements. Be it hard-to-reach areas or large surface areas, whatever the task, you will find the best suitable model.



Model #	RMT 1TD	RMT 3TD	CP 0066	CP 0006	CP 0006 SVR	SBL 05	SBL 06	SBL 06 PE
Weight	2.1 kg / 4.6 lb	5.9 kg / 13 lb	4.5 kg / 10 lb	5.5 kg / 12 lb	6.5 kg / 14 lb	4.5 kg / 10 lb	5.3 kg / 11.5 lb	6.8 kg / 15 lb
Piston Length	111 mm / 4.3"	-	280 mm / 11"	-	-	280 mm / 11"	470 mm / 18.5"	470 mm / 18.5"
Piston Stroke	26.2 mm / 1.3"	26.2 mm / 1.3"	-	-	-	-	-	-
Air pressure	6 bar / 90 psi	6 bar / 90 psi	-	-	-	-	-	-
Blows Per Minute	2400 bpm	7200 bpm	3000	3000 bpm	3000 bpm	2500 bpm	3000 bpm	3000 bpm
Piston Dia	22 mm / 0.8"	22 mm / 0.8"	-	-	-	-	-	-
Air Inlet	3/8"	3/8"	1/2" NPTF	1/2" NPTF	1/2" BSP	-	-	-
Air Hose	9.5 mm / 0.3"	12.7 mm / 0.5"	-	-	-	12.7 mm / 1/2"	12.7 mm / 1/2"	12.7 mm / 1/2"
Air Consumption	8 cfm / 3.7 l/s	15.9 cfm / 7.5 l/s	13 l/s / 27 1/2 cfm	13 l/s / 27 cfm	13 l/s / 27 cfm	13 l/s / 27.5 cfm	13 l/s / 27.5 cfm	13 l/s / 27.5 cfm
Part Number	-	-	8900 0040 05	8900 0040 04	8900 0040 01	8461 0250 13	8461 0250 11	8461 0250 12