

**Tex P60** is most powerful demolition breaker. The drill meets tough requirement of rental industry and likewise other industry demanding powerful breaker. It is most suitable for hard reinforced concrete and other tasks where real power is a must.



## What is good about it?

- Integrated lubrication
- Air cushioned piston
- Controlled power
- Reduced wear
- One piece solid cast housing ensure less maintenance cost

## Where it is used?

- Demanding construction sites

## Specification

| Model #                              | Tex P60S (60 lb class) |                 |
|--------------------------------------|------------------------|-----------------|
| Weight with silencer                 | 33 kg                  | 73 lb           |
| Weight without silencer              | 31 kg                  | 68 lb           |
| Length                               | 690 mm                 | 27.2"           |
| Air pressure                         | 7 bar                  | 102 psi         |
| Air consumption                      | 36 l/s                 | 76 cfm          |
| Blows per minute                     | 1500                   |                 |
| Shank size (standard) - 8461 0227 23 | 28 x 160 mm            | 1 1/8" x 6 1/4" |
| Shank size (option)- 8461 0227 20    | 32 x 160 mm            | 1 1/4" x 6 1/4" |
| Retainer type                        | Latch                  |                 |

\* Available with or without muffler / silencer.



Working Tools



Lubricator



Spare Parts

