



## What is good about it?

- 360° rotation or convenient drilling at any angle
- Automatic rod clamp for easy rod handling
- Drifter directional control with reverse / forward
- Feed motor with reverse / forward direction control
- Water connection or hold flushing
- Lateral movement for parallel drilling
- Integrated oil lubricator and oil flow control
- Automatic rod clamp for easy rod handling
- Water connection or hole flushing

## Where it is used?

- Percussion drill machine for tunnelling
- Drifting & long hole drilling
- Cable bolting or roof supports
- Works in 3 meter height

## Specification

Model #	Simba Junior (Lateral)	
Weight	1050 kg	2315 lb
Pneumatic drifter	RMT 120F	
Hole diameter (Opt 1)	34 – 64 mm	1.3 - 2.5"
Hole diameter (Opt 2)	64 – 75 mm	2.5 - 3"
Drill rod size	R32, R38, T38	
Drill rod length	1.20 metres	4 ft
Drilling length	Opt 1 - 30 mtr	98 ft
	Opt 2 - 15 mtr	49 ft
Air consumption	400 cfm	189 l/s
Drilling rate	1 meter in 4 minutes	
Feed beam	Screw feed type RMT-46	
Rod catcher	Pneumatic type S -10	
Ring size	1500 mm	59"
Dimension (L x W x H)	1780 x 1550 x 2600 mm	70" x 61" x 102"
Column bar height	Closed – 2200 mm, Open – 3700 mm	Closed – 87", Open – 146"



Working Tools



Lubricator



Spare Parts

