



RMT 4123



RMT 4125



RMT 4130



CP 4131



TEX 03 PS



TEX 05 P



CP 0012



CP 0016



CP 0017 SVR

CHIPPING HAMMER

With highest specific BPM, RAMA MINING TOOLS range of Chipping Hammers / chippers are available in **2", 3" and 4" stroke**. It is also available with **Hex or Round shank**. These are most suitable for light surface renovation on soft material such as tile removal, swimming pool renovations, chipping, cutting and trimming etc. Comfort and safety of operator is placed on top without compromising on the sheer power of this Pneumatic Chipping Hammer. Most commonly used in **Foundry and Forge shops** and Mining and construction related **light and medium-hard renovation and construction tasks**.

Model #	RMT 4123 2H / 2R	RMT 4123 3H / 3R	RMT 4123 4H / 4R	RMT 4125 2H / 2R	RMT 4125 3H / 3R	RMT 4125 4H / 4R	RMT 4130 2H / 2R	RMT 4130 3H / 3R	RMT 4130 4H / 4R	CP 4131 3H / 3R	TEX 03 PS	TEX 05 P	CP 0012	CP 0016	CP 0017 SVR
Technically equivalent to	CP 4123 2H / 2R	CP 4123 3H / 3R	CP 4123 4H / 4R	CP 4125 2H / 2R	CP 4125 3H / 3R	CP 4125 4H / 4R	CP 4130 2H / 2R	CP 4130 3H / 3R	CP 4130 4H / 4R	Original only	Original only	Original only	Original only	Original only	Original only
Weight	7 kg	8 kg	8.65 kg	7 kg	7.6 kg	8.4 kg	8.4 kg	9 kg	9.4 kg	8.5 kg	4 kg	5.5 kg	5.5 kg	8.5 kg	9.5 kg
Length	375 mm	426 mm	460 mm	380 mm	430 mm	455 mm	356 mm	387 mm	419 mm	420 mm	300 mm	380 mm	406 mm	420 mm	540 mm
Air pressure	6.2 bar	6.2 bar	6.2 bar	6.2 bar	6.2 bar	6.2 bar	6.2 bar	6.2 bar	6.2 bar	6.2 bar	7 bar	7 bar	6.2 bar	6.2 bar	6.2 bar
Air consumption	13.6 l/s	14 l/s	14 l/s	15.5 l/s	16 l/s	16.5 l/s	14 l/s	15.5 l/s	16 l/s	16 l/s	6.9 l/s	9.5 l/s	9.5 l/s	12 l/s	17 l/s
Blows per minute	2500	2050	1600	2100	1650	1375	3600	2280	1800	1920	4080	2760	2580	1920	1770
Piston dia	28.6 mm	28.6 mm	28.6 mm	28.6 mm	28.6 mm	28.6 mm	28.6 mm	28.6 mm	28.6 mm	28.6 mm	-	-	-	-	-
Piston stroke	50.8 mm	76.2 mm	101.6 mm	50.8 mm	76.20 mm	101.6 mm	50.8 mm	76.2 mm	101.6 mm	95.3 mm	-	-	-	-	-
Air inlet	9.5 mm BSP	9.5 mm BSP	9.5 mm BSP	9.5 mm BSP	9.5 mm BSP	9.5 mm BSP	22.2 mm UNS	22.2 mm UNS	22.2 mm UNS	19 mm	-	-	19 mm BSP	9.5 mm BSP	9.5 mm BSP
Shank size (Hex)	14.7 mm	14.7 mm	14.7 mm	14.7 mm	14.7 mm	14.7 mm	14.7 mm	14.7 mm	14.7 mm	14.7 mm	19 X 50 mm	19 X 50 mm	19 x 50 mm	19 X 50 mm	19 X 50 mm
Shank size (Round)	17.3 mm	17.3 mm	17.3 mm	17.3 mm	17.3 mm	17.3 mm	17.3 mm	17.3 mm	17.3 mm	17.3 mm	-	-	-	-	-
Retainer type	Spring	Spring	Spring	Spring	Spring	Spring	Spring	Spring	Spring	Spring	Quick change	Screw cap	Screw cap	Screw type	Screw cap

Model #	RMT 4123 2H / 2R	RMT 4123 3H / 3R	RMT 4123 4H / 4R	RMT 4125 2H / 2R	RMT 4125 3H / 3R	RMT 4125 4H / 4R	RMT 4130 2H / 2R	RMT 4130 3H / 3R	RMT 4130 4H / 4R	CP 4131 3H / 3R	TEX 03 PS	TEX 05 P	CP 0012	CP 0016	CP 0017 SVR
Technically equivalent to	CP 4123 2H / 2R	CP 4123 3H / 3R	CP 4123 4H / 4R	CP 4125 2H / 2R	CP 4125 3H / 3R	CP 4125 4H / 4R	CP 4130 2H / 2R	CP 4130 3H / 3R	CP 4130 4H / 4R	Original only	Original only	Original only	Original only	Original only	Original only
Weight	15 lb	17.65 lb	19 lb	15.4 lb	16.75 lb	18.5 lb	18.5 lb	20 lb	21 lb	19 lb	8.8 lb	12.1 lb	12 lb	18.8 lb	21 lb
Length	14.8"	16.75"	18.1"	15"	17"	19"	14"	15.25"	16.50"	16½"	11.8"	15"	16"	16.5"	21"
Air pressure	90 psi	90 psi	90 psi	90 psi	90 psi	90 psi	90 psi	90 psi	90 psi	90 psi	102 psi	102 psi	90 psi	90 psi	90 psi
Air consumption	29 cfm	30 cfm	30 cfm	33 cfm	34 cfm	35 cfm	30 cfm	33 cfm	34 cfm	25 cfm	15 cfm	0.34 cfm	20 cfm	26 cfm	36 cfm
Blows per minute	2500	2050	1600	2100	1650	1375	3600	2280	1800	1920	4080	2760	2580	1920	1770
Piston dia	1.13"	1.13"	1.13"	1.13"	1.13"	1.13"	1.13"	1.13"	1.13"	1.13"	-	-	-	-	-
Piston stroke	2"	3"	4"	2"	3"	4"	2"	3"	4"	3¾"	-	-	-	-	-
Air inlet	¾" BSP	¾" BSP	¾" BSP	¾" BSP	¾" BSP	¾" BSP	⅞" UNS	⅞" UNS	⅞" UNS	¾"	-	-	¾" BSP	¾" BSP	¾" BSP
Shank size (Hex)	0.580"	0.580"	0.580"	0.580"	0.580"	0.580"	0.580"	0.580"	0.580"	0.580"	¾" x 2"	¾" x 2"	¾" x 2"	¾" x 2"	¾" x 2"
Shank size (Round)	0.680"	0.680"	0.680"	0.680"	0.680"	0.680"	0.680"	0.680"	0.680"	0.680"	-	-	-	-	-
Retainer type	Spring	Spring	Spring	Spring	Spring	Spring	Spring	Spring	Spring	Spring	Quick change	Screw cap	Screw cap	Screw cap	Screw cap

CP = Chicago Pneumatic | Tex = Atlas Copco

All above hammers are available with or without mufflers / silencers