

The **RMT 3/30 SD** is a lightweight **25 kg** pneumatic sinker drill, fully equivalent to the **Holman Silver 3**, designed for vertical downward drilling in mines, quarries, tunnels, and construction sites. It delivers a powerful **2400 blows per minute** at 6 bar, capable of drilling up to **32 mm hole diameter** at depths of **3-4 metres** in hard rock. Lighter in weight yet higher in torque than comparable drills in its class, it reduces operator fatigue while maintaining strong penetration rates. It features a **robust kick-latch retainer** for fast drill rod changes and is backed by economical, fully interchangeable spare parts for lower cost-per-metre drilled.



What is good about it?

- Lighter in weight
- Higher in torque
- Economical as low consumption of spare parts
- Kick Latch type retainer

Where it is used?

- Mines and Quarry
- Tunneling
- Metal Mines
- Marble Mines
- Dams
- Shaft Sinking

Specification

Model #	RMT 3/30 SD	
Technically equivalent to	Silver 3 of Holman	
Weight	25 kg	55 lb
Length	610 mm	24"
Hole range (upto)	32 mm	1.25"
Hole depth (max.)	3 to 4 mtr	10 to 12 ft.
Air pressure	6 bar	87 psi
Air consumption	46 l/s	97 cfm
Blows per minute	2400	
Piston dia	76 mm	3"
Piston stroke	51 mm	2"
Shank size	22 x 108 mm	7/8" x 4 1/4"



Working Tools



Lubricator



Spare Parts