



RMT 4608 D



RMT 4611 D



RMT 4608 P



RMT 4611 P



RMT 4689



RMT 133 D



RMT 1133 D



TEX 14 D



TEX 14 P



TEX 15 D



TEX 15 P

## RIVET BUSTER

RMT **Rivet Busters** are a Combination of lowest specific bpm, high power, and lighter weight. Rivet Buster Teasing Throttle and Low Blow Frequency give the operator total control of the Rivet Buster tool. All RMT busters have **stepped cylinder** which prevents accidental ejection of the piston from the cylinder, making it absolutely safe for the operator. Our **Rivet Busters** provide the same performance as a breaker of double the weight of the buster would have provided. Our busters are available with **8" and 11" stroke with 'D' Handle and 'P' handle** . It is used in Concrete and Metal applications such as bridge deck work, de-capping foundation pillars, cutting and removing large rivets and bolts, cutting metal tanks or plates, etc..

Model #	RMT 4608 D	RMT 4611 D	RMT 4608 P	RMT 4611 P	RMT 133 D	RMT 1133 D	TEX 14 D	TEX 14 P
Weight (kg / lb)	14.4 kg (31.7 lb)	15.4 kg (34 lb)	14 kg (30.9 lb)	15 kg (33 lb)	13.6 kg (30 lb)	15.7 kg (34.7 lb)	14.1 kg (31 lb)	13.7 kg (30 lb)
Length (mm / inch)	600 mm (23.6")	676 mm (26.6")	584 mm (23")	660 mm (26")	570 mm (22.5")	648 mm (25¼")	600 mm (23.6")	584 mm (23")
Blows per minute	900	720	900	720	1140	850	900	900
Piston stroke (mm / inch)	203 mm (8")	279 mm (11")	203 mm (8")	279 mm (11")	203 mm (8")	279 mm (11")	203 mm (8")	203 mm (8")
Air consumption (ls / cfm)	21 l/s (44.5 cfm)	21 l/s (44.5 cfm)	21 l/s (44.5 cfm)	21 l/s (44.5 cfm)	19.8 - 21.7 ls (42-46 cfm)	22.6 l/s (48-52 cfm)	21 l/s (44 cfm)	21 l/s (44 cfm)
Air pressure (bar / psi)	6.2 bar (90 psi)	6.2 bar (90 psi)	6.2 bar (90 psi)	6.2 bar (90 psi)	-	-	-	-
Piston dia (mm / inch)	30.2 mm (1.19")	30.2 mm (1.19")	30.2 mm (1.19")	30.2 mm (1.19")	-	-	-	-
Air inlet (NPTF thread) (mm / inch)	12.7 mm (½")	12.7 mm (½")	12.7 mm (½")	12.7 mm (½")	12.7 mm (½")	12.7 mm (½")	-	-
Shank size	Jumbo	Jumbo	Jumbo	Jumbo	Jumbo	Jumbo	Jumbo	Jumbo
Reference #	8900 0001 51	8900 0001 52	8900 0001 49	8900 0001 50	5216	17399	8461 0250 17	8461 0250 16

Model #	TEX 15 D	TEX 15 P
Weight (kg / lb)	15.4 kg (34 lb)	15 kg (33 lb)
Length (mm / inch)	676 mm (26.6")	660 mm (26")
Blows per minute	720	720
Piston stroke (mm / inch)	279 mm (11")	279 mm (11")
Air consumption (ls / cfm)	21 l/s (44 cfm)	21 l/s (44 cfm)
Air pressure (bar / psi)	-	-
Piston dia (mm / inch)	-	-
Air inlet (NPTF thread) (mm / inch)	12.7 mm (½")	12.7 mm (½")
Reference #	Jumbo	Jumbo
Shank size	8461 0250 19	8461 0250 18

Model #	RMT 4689 B50	RMT 4689 B60	RMT 4689 B60
Weight (kg / lb)	9.2 kg (20.3 lb)	10 kg (22 lb)	10.8 kg (23.8 lb)
Length (mm / inch)	430 mm (16.9")	470 mm (18.5")	523 mm (20.6")
Blows per minute	1500	1320	1200
Riveting capacity in steel	20 mm (0.39")	24 mm (0.94")	30 mm (1.18")
Air inlet (NPTF thread)	12.7 mm (½")	12.7 mm (½")	12.7 mm (½")
Type of handle	Pistol Grip	Pistol Grip	Pistol Grip
Standard equipment	Snap Clip Retainer	Snap Clip Retainer	Snap Clip Retainer