

The low weight of **RMT 1210 Paving Breaker** makes it very easy for users to operate the tool. Despite its low weight, it hits the surface hard and performs even in most challenging working conditions. This air tool is most suitable for light to medium construction work like demolition of floors, pavement, asphalt, frozen ground etc. It is also used for Bridge maintenance and deck jobs. Four bolt backhead ensures minimum servicing to hammer which gives continuous usage of the tool.



What is good about it?

- with 100% parts interchangeability
- Robust yet, light weight
- Forged, heat treated all alloy steel construction or excellent durability
- Four-bolt backhead – withstands rugged use
- “Goose neck” Air Inlet Swivel for easy handling and positioning

Where it is used?

- Light to medium construction
- Utility and plat maintenance work such as demolition of floors, pavements and road surface
- Bridge deck jobs

Specification

Model #	RMT 1210 (35 lb class)	
Weight with silencer	20 kg	44 lb
Weight without silencer	19.4 kg	42.7 lb
Length	609 mm	24"
Air pressure	6 bar	87 psi
Air consumption	23 l/s	48 cfm
Blows per minute	1450	
Piston dia	48 mm	1.90"
Piston stroke	108 mm	4¼"
Air inlet (BSP thread)	19 mm	¾"
Shank size (standard) - 8900 0030 04	25 x 108 mm	1" x 4¼"
Retainer type	Latch	

*Available with or without noise reducing silencer / muffler


Working Tools
Lubricator
Spare Parts

11 Dec 2023 / RMT-100.01.01