

PICK HAMMER

Rama Mining Tools Pick Hammers are the right mix of low weight and high productivity. Hammers with "D" type handles are most productive in the medium weight class. These pick hammers give the same level of high production under the toughest of conditions, delivering power with precision. These pick hammers are mostly used in renovation works such as removing a section of brick walls, renovating concrete floors. It is also used in construction or rock breaking, heavy-duty chipping and cutting, etc. An ideal tool for challenging job sites.



Model #	RMT 12 PS	TEX 09 PS	TEX 10 PS	TEX 09 PE	TEX 10 PSKL
Weight (kg / lb)	10.5 kg / 23.1 lb	10 kg / 22 lb	10 kg / 22 lb	10.5 kg / 23.1 lb	10.5 kg / 23 lb
Length (mm / inch)	550 mm / 21.7"	500 mm / 19.7"	520 mm / 20.5"	560 mm / 22"	500 mm / 19.7"
Air pressure (bar / psi)	-	7 bar / 102 psi	7 bar / 102 psi	-	7 bar / 102 psi
Air consumption (ls / cfm)	21.3 l/s / 45 cfm	18.5 l/s / 39 cfm	17 l/s / 36 cfm	17 l/s / 36 cfm	17 l/s / 36 cfm
Blows per minute	1600	1800	1350	1800	1350
Piston dia (mm / inch)	-	-	-	-	-
Air inlet (BSP thread)	-	-	-	-	-
Shank size (mm / inch) - Hex	22 x 82.5 mm / 7/8" x 3 1/4"	22 x 82.5 mm / 7/8" x 3 1/4"	22 x 82.5 mm / 7/8" x 3 1/4"	22 x 82.5 mm / 7/8" x 3 1/4"	22 x 82.5 mm / 7/8" x 3 1/4"
Shank size (mm / inch) - Rd	25 x 75 mm / 1" x 3"	25 x 75 mm / 1" x 3"	25 x 75 mm / 1" x 3"	25 x 75 mm / 1" x 3"	-
Retainer type	Cap	Cap	Cap	Latch	Kick latch

PICK HAMMER

Rama Mining Tools Pick Hammers are the right mix of low weight and high productivity. Hammers with "D" type handles are most productive in the medium weight class. These pick hammers give the same level of high production under the toughest of conditions, delivering power with precision. These pick hammers are mostly used in renovation works such as removing a section of brick walls, renovating concrete floors. It is also used in construction or rock breaking, heavy-duty chipping and cutting, etc. An ideal tool for challenging job sites.



Model #	CP 0122	TEX 12 PS	TEX 09 PSKL	TEX 12 PE	TEX 12 PSKL
Weight (kg / lb)	11 kg / 24 lb	10.5 kg / 23.1 lb	12 kg / 26.5 lb	12 kg / 26.5 lb	12.5 kg / 27.6 lb
Length (mm / inch)	495 mm / 19.5"	550 mm / 21.7"	500 mm / 19.7"	590 mm / 23.2"	545 mm / 21.5"
Air pressure (bar / psi)	-	-	7 bar / 102 psi	-	-
Air consumption (ls / cfm)	21 l/s / 44.5 cfm	21.3 l/s / 45 cfm	18.5 l/s / 39 cfm	20 l/s / 0.71 cfm	21.3 l/s / 45 cfm
Blows per minute	1320	1600	1800	1620	1600
Piston dia (mm / inch)	40 mm / 1.60"	-	-	-	-
Air inlet (BSP thread)	19 mm / ¾"	-	-	-	-
Shank size (mm / inch) - Hex	22 x 82.5 mm / 7/8" x 3¼"	22 x 82.5 mm / 7/8" x 3¼"	22 x 82.5 mm / 7/8" x 3¼"	22 x 82.5 mm / 7/8" x 3¼"	22 x 82.5 mm / 7/8" x 3¼"
Shank size (mm / inch) - Rd	-	25 x 75 mm / 1" x 3"	-	25 x 75 mm / 1" x 3"	25 x 75 mm / 1" x 3"
Retainer type	Screw cap	Cap	Kick latch	Cap	Kick latch