



### What is good about it?

- 360° rotation for convenient drilling at any angle
- Automatic rod clamp for easy rod handling
- Drifter directional control with reverse / forward
- Feed motor with reverse / forward direction control
- Water connection or hold flushing
- Lateral movement for parallel drilling
- Integrated oil lubricator and oil flow control
- Automatic rod clamp for easy rod handling
- Water connection or hole flushing

### Where it is used?

- Percussion drill machine for tunnelling
- Drifting & long hole drilling
- Cable bolting or roof supports
- Works in 3 meter height

### Specification

Model #	Simba Junior (Standard)	
Weight	850 kg	1874 lb
Pneumatic drifter	RMT 120F	
Hole diameter	48 - 57 mm	1.9" - 2¼"
Drill rod size	R32	
Drill rod length	1.20 metres	4ft
Drilling length	25 mtr. max.	82ft
Air consumption	400 cfm	189 l/s
Drilling rate	1 meter in 4 minutes	
Feed beam	Screw feed type RMT-46	
Rod catcher	Pneumatic type RSP-10	
Ring size	1500 mm	59"
Dimension(L x W x H)	1780 x 1550 x 2600 mm	70" x 61" x 102"
Column bar height	Closed – 2200 mm, Open – 3700 mm	Closed – 87", Open – 146"



Working Tools



Lubricator



Spare Parts

