

The CP 0022 is a compact, 15 kg (33 lbs) pneumatic rock drill designed for high mobility and low air consumption. It features a combined blower and throttle lever for simple, one-lever operation and is available in two shank sizes to fit existing inventory. This tool is best suited for light-duty rock drilling, public utility jobs, works maintenance, and elevated drilling from scaffolding or in tight spaces. Supplied through RMT, it provides a dependable, easy-to-handle solution supported by readily stocked authentic and compatible spare parts.

What is good about it?


- Light weight and powerful
- Very easy mobility
- Low air consumption
- Combined blower and throttle lever for easy control

Where it is used?

- Works maintenance
- Public utilities
- Drilling from scaffolding

Specification

Model #	CP 0022	
Weight	15 kg	33 lb
Length	475 mm	18.7"
Hole range (upto)	40 mm	1.57"
Hole depth (max.)	2.4 meters	7.9 ft
Air pressure	6.2 bar	90 psi
Air consumption	22 l/s	47 cfm
Blows per minute	2220	
Revolutions	232 rpm	
Piston dia	60 mm	2.36"
Piston stroke	44 mm	1.75"
Air inlet (Swivel)	19 mm	¾"
Shank Size - 8900 0020 01	22 x 82.5 mm	⅞" X 3¼"
Shank size (optional)	22 x 108 mm	⅞" x 4¼"



Working Tools



Lubricator



Spare Parts