

The 10 Litre Lubricator serves as a cost-effective alternative to the original model 8202 5102 40, providing continuous lubrication for pneumatic hammers and drills to ensure smooth operation and prevent premature part damage. Its highly durable turtle-shaped design features a 210 mm outside diameter and a height up to 585 mm, including an oil control key for flow adjustment and fitted claw couplings for easy hose attachment. Available in variants from 10 L to 10 LD, this 2.2-gallon capacity range supports hose connections up to 63.5 mm, airflows reaching 423 l/s, and maximum pressures up to 24.13 bar. As part of RMT's wide selection ranging from 1.3 L to 15 L, these units are ideal for high-demand usage and should be paired with the RMT Safety Whipchek to ensure maximum user safety.



Specification

Model #	10 L	10 LA	10 LB	10 LC	10 LD
Oil Volume	10 ltr / 2.2 gal	10 ltr / 2.2 gal	10 ltr / 2.2 gal	10 ltr / 2.2 gal	10 ltr / 2.2 gal
Hose connection	50.8 mm / 2"	50.8 mm / 2"	50.8 mm / 2"	50.8 mm / 2"	63.5 mm / 2½"
Air flow	282 ls / 600 cfm	352.5 ls / 750 cfm	423 ls / 900 cfm	423 ls / 900 cfm	423 ls / 900 cfm
Max pressure	10.34 bar / 150 psi	17.24 bar / 250 psi	17.24 bar / 250 psi	24.13 bar / 350 psi	24.13 bar / 350 psi
Height	580 mm / 22.8"	585 mm / 23"	585 mm / 23"	585 mm / 23"	585 mm / 23"
Outside dia	210 mm / 8.3"	210 mm / 8.3"	210 mm / 8.3"	210 mm / 8.3"	210 mm / 8.3"

14 Oct 2026

