

The 15 Litre Lubricator is a highly durable, cost-effective alternative to the original model 8202 5102 40, designed to continuously lubricate pneumatic hammers and drills to prevent friction-related damage and ensure smooth operation. Its turtle-shaped design stands 725 mm tall and includes an oil control key to adjust flow as needed, along with fitted claw couplings for easy hose attachment. Available in variants from 15 L to 15 LF, this 3.9-gallon capacity range supports hose connections up to 63.5 mm, maximum pressures reaching 24.13 bar, and impressive airflows up to 658 l/s. As the largest unit in RMT's selection, it is ideal for high-demand operations and should be paired with the RMT Safety Whipchek for enhanced user safety.



Specification

Model #	15 L	15 LA	15 LB	15 LC	15 LD	15 LE	15 LF
Oil Volume	15 ltr / 3.9 gal	15 ltr / 3.9 gal	15 ltr / 3.9 gal	15 ltr / 3.9 gal	15 ltr / 3.9 gal	15 ltr / 3.9 gal	15 ltr / 3.9 gal
Hose connection	50.8 mm / 2"	50.8 mm / 2"	50.8 mm / 2"	63.5 mm / 2½"	63.5 mm / 2½"	63.5 mm / 2½"	63.5 mm / 2½"
Air flow	282 ls / 600 cfm	329 ls / 700 cfm	423 ls / 900 cfm	423 ls / 900 cfm	470 ls / 1000 cfm	564 ls / 1200cfm	658 ls / 1400 cfm
Max pressure	10.34 bar / 150 psi	17.24 bar / 250 psi	17.24 bar / 250 psi	24.13 bar / 350 psi	24.13 bar / 350 psi	24.13 bar / 350 psi	24.13 bar / 350 psi
Height	725 mm / 28.54"	725 mm / 28.54"	725 mm / 28.54"	725 mm / 28.54"	725 mm / 28.54"	725 mm / 28.54"	725 mm / 28.54"
Outside dia	210 mm / 8.3"	210 mm / 8.3"	210 mm / 8.3"	210 mm / 8.3"	210 mm / 8.3"	210 mm / 8.3"	210 mm / 8.3"

14 Oct 2026

