

The 3 Litre Lubricator is a cost-effective alternative to the original model 8202 5102 40, serving as a durable container that lubricates pneumatic hammers and drills for smooth operation by reducing friction and preventing premature part damage. Its compact turtle-shaped design (430 mm height, 165 mm diameter) ensures easy handling, with an oil control key to adjust flow and fitted claw couplings for quick hose attachment. Available in variants like 3 L, 3 LA and 3 LB (3 litre / 0.66 gallon volume, hose connections from 38.10–50.80 mm, airflow up to 423 l/s and max pressure up to 24.13 bar), it supports reliable continuous use and pairs with the RMT Safety Whipchek for added safety; RMT offers a full range from 1.3 L to 15 L to meet varying needs.



Specification

Model #	3 L	3 LA	3 LB
Oil Volume	3 ltr / 0.66 gal	3 ltr / 0.66 gal	3 ltr / 0.66 gal
Hose connection	38.10mm / 1½"	38.10mm / 1½"	50.80mm / 2"
Air flow	282 ls / 600 cfm	423 ls / 900 cfm	423 ls / 900 cfm
Max pressure	10.34 bar / 150 psi	13.79 bar / 200 psi	24.13 bar / 350 psi
Height	430 mm / 17"	430 mm / 17"	1"(BSP/NPT)
Outside dia	165 mm / 6.5"	165 mm / 6.5"	165 mm / 6.5"

14 Oct 2026

