

The 5 Litre Lubricator is a cost-effective alternative to the original model 8202 5102 40, serving as a durable container that continuously lubricates pneumatic hammers and drills to ensure smooth operation, reduce friction, and prevent premature part damage. Its ergonomic turtle-shaped design (400 mm height, 209–210 mm outside diameter) ensures easy handling, featuring an oil control key to adjust flow and fitted claw couplings for quick hose attachment. Available in models 5 L and 5 LA with a 5-litre (1.1 gallon) oil volume, it offers hose connections ranging from 50.80 mm to 63.50 mm, airflows up to 423 l/s, and maximum operating pressures up to 13.79 bar. Designed for demanding continuous usage, it can be paired with the RMT Safety Whipchek for enhanced user safety as part of RMT's wide selection of lubricators ranging from 1.3 L to 15 L.



## Specification

| Model #         | 5 L                  | 5 LA                |
|-----------------|----------------------|---------------------|
| Oil Volume      | 5 ltr / 1.1 gal      | 5 ltr / 1.1 gal     |
| Hose connection | 63.50 mm / 1½" or 2" | 50.80 mm / 2"       |
| Air flow        | 282 ls / 600 cfm     | 423 ls / 900 cfm    |
| Max pressure    | 10.34 bar / 150 psi  | 13.79 bar / 200 psi |
| Height          | 400 mm / 15.8"       | 400 mm / 15.8"      |
| Outside dia     | 210 mm / 8.3"        | 209 mm / 8.2"       |

14 Oct 2026

