RAMA MINING TOOLS PVT. LTD.

RMT 3/30 SL
STOPER DRILL

Mining Tools

RMT 3/30 SL is a robust stoper drill designed for underground mining applications, delivering good penetration rates with low air pressure and a short stroke. It is suitable for soft and hard rock penetration, roof bolting, production drilling, and bolt tightening. Operating at 6 bar air pressure with **80 l/s** air consumption, it provides up to **2900 blows per minute** for efficient drilling. The drill supports 32 mm hole diameter and **3-4 m** drilling depth, with a **22 × 108 mm** shank size. Technically equivalent to the Silver 30 of Holman, it offers a dependable replacement option for mining operations.



Specification

Model #	RMT 3/30 SL	
Technically equivalent to	Silver 30 of Holman	
Weight Only Drill	23 kg	51 lb
Weight with leg	40 kg	88 lb
Length retracted	1700 mm	67"
Length extracted	2580 mm	102"
Air pressure	6 bar	87 psi
Air consumption	80 l/s	150 cfm
Blows per minute	2900	
Drilling Depth	3 to 4 meters	10 - 12 ft
Hole dia	32 mm	1.25″
Piston dia	76 mm	3″
Piston stroke	51 mm	2″
Air inlet	19 mm	¾″
Shank size	22 x 108 mm	⅞″x 4¼″
Manufacturer	RMT	

10 Oct 2026



Working Tools



Lubricator



Spare Parts

Premises B1/B2, Rajlaxmi Commercial Complex, Kalher, Bhiwandi, Maharashtra 421302 | +91 98367 54560 | info@rminingtools.com | www.rminingtools.com

Trademarks and part numbers are used for identification purposes only and remain the property of their respective owners. "RMT" products are independent replacements and are not sponsored or authorized by the OEM. "OEM" denotes genuine brand-owner products.