RAMA MINING TOOLS PVT. LTD.

RMT 3/30 JLD

JACKLEG DRILL

Construction / Demolition Tools

Most reliable water flushed **Rock Drill** suitable for underground and tunnel work for horizontal and inclined drilling. Once connected with a **Pusher Leg**, hole from 27 to 46 mm diameter up to 6 meters can be drilling with 22 mm **Drill steel**. The cost of per meter of hole drilled is low because of fast penetration and low consumption of spare parts and air.



What is good about it?

- High Performance
- Reliability
- Economical as low consumption of spare parts

Specification

Model #	RMT 3/30 JLD	
Weight	23 kg	50.71 lb
Weight with leg	58 kg	128 lb
Length	610 mm	24"
Hole dia	32 mm	1.25"
Drilling depth	3 to 4 mtr	10 -12 ft.
Flushing with	Air or Water	
Air inlet (BSP thread)	19 mm	¾"
Air pressure	6 bar	87 psi
Air consumption	57 l/s	120 cfm
Blows per minute	2600	
Piston dia	76 mm	3"
Stroke	51 mm	2"
Shank size	22 x 108 mm	⅞" x 4¼"
Rotation	CCW (Counter Clock Wise)	
Bore	76 mm	3"
Water connection	½" Hose	
Water consumption in Lit/min	20 ltr/minute at 2 - 3 bar pressure	
Theoretical rotating speed	260 rpm	

12 Oct 2026

Where it is used?

- Under Ground Mining
- Tunnel
- Metal Mines



Working Tools



Lubricator



Spare Parts



Premises B1/B2, Rajlaxmi Commercial Complex, Kalher, Bhiwandi, Maharashtra 421302 | +91 98367 54560 | info@rminingtools.com | www.rminingtools.com

Trademarks and part numbers are used for identification purposes only and remain the property of their respective owners. "RMT" products are independent replacements and are not sponsored or authorized by the OEM. "OEM" denotes genuine brand-owner products.

RAMA MINING TOOLS PVT. LTD.

RMT 3/30 JLD

PERFORADORA NEUMÁTICA CON EMPUJADOR

Perforadora neumática para roca con lavado por agua, altamente confiable y adecuada para trabajos subterráneos y túneles, tanto para perforación horizontal como inclinada. Una vez conectada con una columna de empuje (Pusher Leg), se pueden perforar barrenos de 27 a 46 mm de diámetro y hasta 6 metros de profundidad con barra de perforación de 22 mm. El costo por metro perforado es bajo gracias a su alta velocidad de penetración y al bajo consumo de repuestos y aire.



¿Qué tiene de bueno?-

- Alto rendimiento
- Confiabilidad
- Económica gracias al bajo consumo de repuestos

Especificaciones

Modelo#	RMT 3/30 JLD	
Peso – Solo perforadora	23 kg	50.71 lb
Peso – Perforadora + pata	58 kg	128 lb
Longitud - Solo perforadora	610 mm	24"
Diámetro del barreno	32 mm	1.25"
Profundidad de perforación	3 to 4 mtr	10 -12 ft.
Lavado	Aire o agua	
Entrada de aire (rosca BSP)	19 mm	¾"
Presión de aire	6 bar	87 psi
Consumo de aire	57 l/s	120 cfm
Golpes por minuto	2600	
Diámetro del pistón	76 mm	3"
Carrera	51 mm	2"
Tamaño del vástago	22 x 108 mm	⅞" x 4¼"
Rotación	CCW (sentido antihorario)	
Diámetro interior	76 mm	3"
Conexión de agua	½" Hose	
Consumo de agua en lit./min.	20 ltr/minute at 2 - 3 bar pressure	
Velocidad teórica de rotación	260 rpm	

¿Dónde se utiliza?

- Minería subterránea
- Túneles
- Minas de metales


Herramientas de trabajo


Lubricador


Repuestos

12 Oct 2026



Premises B1/B2, Rajlaxmi Commercial Complex, Kalher, Bhiwandi, Maharashtra 421302 | +91 98367 54560 | info@rminingtools.com | www.rminingtools.com

Trademarks and part numbers are used for identification purposes only and remain the property of their respective owners. "RMT" products are independent replacements and are not sponsored or authorized by the OEM. "OEM" denotes genuine brand-owner products