RAMMERS / TAMPERS

RAMA MINING TOOLS PVT. LTD.

Rammers are perfect compacting soil and sand in such applications as foundry molds, backfilling foundations, pipe work, and cable trenching, these tools are built to with stand heavy use in tough environments and include effective seal designs that keep internal components free from dirt and grit.



Model #	RMT T 172	RMT R115	RMT R215	RMT TAM 14	RMT 0003	RMT 0004 RV	CP 0003	CP 0004 RV
OEM Model	-	-	-	TAM 14 Atlas Copco (8461 0250 14)	CP 0003 (8900 0040 06)	CP 0004 RV (8900 0040 03)	CP 0003 (8900 0040 06)	CP 0004 RV (8900 0040 03)
Weight (kg / lb)	2.3 kg / 5 lb	4 kg / 9.25 lb	10.9 kg / 49.82 lb	13.6 kg / 30 lb	13.6 kg / 30 lb	19 kg / 42 lb	13.6 kg / 30 lb	19 kg / 42 lb
Length (mm / inch)	280 mm / 11"	460 mm / 18"	1156 mm / 45.5"	1320 mm / 52"	1320 mm / 52"	1270 mm / 50"	1320 mm / 52"	1270 mm / 50"
Air pressure (bar / psi)	6 bar / 90 psi	6 bar / 90 psi	6 bar / 90 psi	6 bar / 90 psi	6 bar / 90 psi	6 bar / 90 psi	6 bar / 90 psi	6 bar / 90 psi
Air consumption (l/s / cfm)	–	7 l/s / 15 cfm	11.8 l/s / 25 cfm	8.4 l/s / 18 cfm	8.4 l/s / 18 cfm	13 l/s / 27.5 cfm	8.4 l/s / 17.7 cfm	13 l/s / 27.5 cfm
Blows per minutes	1800	850	800	800	800	780	800	780
Piston stroke (mm / inch)	–	102 mm / 4"	203 mm / 8"	–	152 mm / 6"	152 mm / 6"	152 mm / 6"	152 mm / 6"
Air inlet (BSP) (mm / inch)	9.5 mm / ⅜"	9.5 mm / ⅜"	12.7 mm / ½"	12.7 mm / ½"	12.7 mm / ½"	12.7 mm / ½"	12.7 mm / ½"	12.7 mm / ½"
Butt Size & Type	–	63.5 mm / 2.5" (Rubber)	63.5 mm / 2.5" (Steel)	127 mm / 5"	127 mm / 5"	158.75 mm / 6¼"	25.4 mm / 1"	158.75 mm / 6¼"

info@rminingtools.com | www.rminingtools.com | Premises B1/B2, Rajlaxmi Commercial Complex, Kalher, Bhiwandi, Maharashtra 421302

Trademarks and part numbers are used for identification purposes only and remain the property of their respective owners. "RMT" products are independent replacements and are not sponsored or authorized by the OEM. "OEM" denotes genuine brand-owner products.

RAMMERS / TAMPERS

RAMA MINING TOOLS PVT. LTD.



Model #	TAM 19
OEM Model	TAM 19 Atlas Copco (8461 0250 15)
Weight (kg / lb)	19 kg / 41.8 lb
Length (mm / inch)	1270 mm / 50”
Air pressure (bar / psi)	6 bar / 90 psi
Air consumption (l/s / cfm)	73 l/s / 156 cfm
Blows per minutes	780
Piston stroke (mm / inch)	–
Air inlet (BSP) (mm / inch)	19 mm / ¾"
Butt Size & Type	158.8 mm / 5"

22 Oct 2026

info@rminingtools.com | www.rminingtools.com | Premises B1/B2, Rajlaxmi Commercial Complex, Kalher, Bhiwandi, Maharashtra 421302

Trademarks and part numbers are used for identification purposes only and remain the property of their respective owners. "RMT" products are independent replacements and are not sponsored or authorized by the OEM. "OEM" denotes genuine brand-owner products.